Product datasheet

Specification





module XPSAC - Emergency stop - 115 V AC

XPSAC3421

- ! Discontinued on: 31 Dec 2023
- ! To be end-of-service on: 31 Dec 2025

① Discontinued

Price: 7,797.18 ZAR

Main

Range Of Product	Preventa Safety automation
Product Or Component Type	Preventa safety module
Safety Module Name	XPSAC
Safety Module Application	For emergency stop and switch monitoring
Function Of Module	Switch monitoring Emergency stop
Safety Level	Can reach PL e/category 4 conforming to EN/ISO 13849-1 Can reach SILCL 3 conforming to EN/IEC 62061
Safety Reliability Data	MTTFd = 210.4 years conforming to EN/ISO 13849-1 DC > 99 % conforming to EN/ISO 13849-1 PFHd = 3.56E-9 1/h conforming to EN/IEC 62061
Type Of Start	Unmonitored
Connections - Terminals	Captive screw clamp terminals, 1 x 0.141 x 2.5 mm² flexible with cable end, with double bezel Captive screw clamp terminals, 1 x 0.141 x 2.5 mm² solid with cable end, with double bezel Captive screw clamp terminals, 1 x 0.251 x 1.5 mm² flexible with cable end, with double bezel Captive screw clamp terminals, 1 x 0.251 x 2.5 mm² flexible with cable end, with double bezel Captive screw clamp terminals, 2 x 0.142 x 0.75 mm² flexible with cable end, with double bezel Captive screw clamp terminals, 2 x 0.142 x 0.75 mm² solid with cable end, with double bezel Captive screw clamp terminals, 2 x 0.142 x 0.75 mm² flexible with cable end, with double bezel Captive screw clamp terminals, 2 x 0.252 x 1 mm² flexible with cable end, with double bezel Captive screw clamp terminals, 2 x 0.52 x 1.5 mm² flexible with cable end, with double bezel
Output Type	Relay instantaneous opening, 3 NO circuit(s), volt-free
Number Of Additional Circuits	1 solid state output
[Us] Rated Supply Voltage	115 V AC - 1515 %

Complementary

Supply Frequency	50/60 Hz	
Maximum Power Consumption In Va	7 VA AC	
[Uc] Control Circuit Voltage	115 V	
Breaking Capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush AC-15 C300 relay output	
Breaking Capacity	1.5 A at 24 V (DC-13) time constant: 50 ms for relay output	

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Output Thermal Current	6 A per relay for relay output
[Ith] Conventional Free Air Thermal Current	10.5 A
Associated Fuse Rating	4 A gG or gL for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200 6 A fast blow for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum Output Current	10 mA for relay output
Minimum Output Voltage	16 V for relay output
Maximum Response Time On Input Open	100 ms
[Ui] Rated Insulation Voltage	300 V (pollution degree 2) conforming to IEC 60947-5-1 300 V (pollution degree 2) conforming to DIN VDE 0110 part 1
[Uimp] Rated Impulse Withstand Voltage	4 kV overvoltage category III conforming to IEC 60947-5-1 4 kV overvoltage category III conforming to DIN VDE 0110 part 1
Local Signalling	2 LEDs
Current Consumption	60 mA at 115 V AC on power supply
Mounting Support	35 mm symmetrical DIN rail
Net Weight	0.21 kg
Environment	
Standards	EN/ISO 13850 EN/IEC 60947-5-1

Standards	EN/ISO 13850 EN/IEC 60947-5-1 EN 60204-1 EN 1088/ISO 14119
Product Certifications	CSA TÜV UL
Ip Degree Of Protection	IP20 (terminals) conforming to EN/IEC 60529 IP40 (enclosure) conforming to EN/IEC 60529
Ambient Air Temperature For Operation	-1055 °C
Ambient Air Temperature For Storage	-2585 °C

Packing Units

r doming office	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	10.3 cm
Package 1 Length	12.0 cm
Package 1 Weight	242.0 g
Unit Type Of Package 2	S01
Number Of Units In Package 2	16
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.169 kg

Contractual warranty

Warranty

18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free	
	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards

Circularity Profile	End of Life Information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Environmental Disclosure	Product Environmental Profile
China Rohs Regulation	China RoHS declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Reach Regulation	REACh Declaration